

John F. Kennedy Space Center

Mine Test of a Cryogenic Refuge Alternative Supply System (CryoRASS)

Donald Doerr, Ed Blalock, and David Bush

LABTECH Inc., BCS Life Support LLC, and NASA


10 February 2015

Refuge Alternatives Partnership Meeting

This effort is completed as part of CDC Inter-Agency Agreement (IAA/SAA):-
CDC Agreement No: 12FED1213259, NASA SAA No: KCA-4357



Cryogenic Refuge Alternative Supply System




John F. Kennedy Space Center

Why use liquid air?

- Provide a new technology method for air storage
- Store more air in less space to reduce size & weight
- Store air at lower pressure to improve safety
- Provide heat stress relief to improve comfort & survivability – reduce temperature and humidity




Basic Design considerations




John F. Kennedy Space Center

- Store 96 hours of air supply in liquid form
 - Use 2 x 425 liter + 300 liter dewars for a 23 man chamber
- Preserve quantity and composition of liquid air
 - Use cryocooler to overcome heat leak during long term storage
 - Assume electrical power until emergency
 - Assume no electrical power during emergency
- Simple activation by first miner to enter (1 pull)
- Provide air at 5X oxygen quantity (1.32 ft³/hr/person)
- Provide cooling for heat stress relief
- Provide dehumidification for heat stress relief
- Provide air circulation within refuge
- Provide partial CO₂ flushing





Sustainability of Liquid Air




John F. Kennedy Space Center


- Liquid air composition and quantity can be maintained with use of cryocooler
 - Instrumented studies for 6 months show no change
 - Cryocooler for 425 liter dewar requires 7.2 amp/240VAC
- For this test, all three dewars filled on 6 November
- Dewars shipped on 10/11 November – 300 liter cryocooler damaged
- Dewars in mine 12 November – 2 cryocoolers operating (425's)
- Test started 17 November with 300 liter
 - 11 days after fill
 - 7 days after cryocooler failed
- Dewar is self pressurizing with buildup loop, regulator controls pressure at 75 psi



First 96 hour test of CryoRASS




John F. Kennedy Space Center



Trinity Refuge Alternative - 10 person



How much liquid air for 23 person inflatable refuge?




John F. Kennedy Space Center


- MSHA requirement = 1.32 ft^3 oxygen/ hour/person
 - X5 = $6.6 \text{ ft}^3/\text{hr}$ since O_2 is ~20% component of air
 - for 23 miners = $152 \text{ ft}^3/\text{hr}$
 - for 96 hours = $14,575 \text{ ft}^3$ (total)
 - gaseous flow rate = $4300 \text{ liters/hr} = 72 \text{ liters/minute}$ (minimum)(2.5 SCFM)
- Volumetric expansion ration for liquid to gaseous air = 728 : 1
 - total liquid required = 20 ft^3 or 566 liters
 - → **minimum** flow to air handler = 72 liters/minute (gaseous)(2.5 SCFM)
 - to provide maximum duration (165 hr)
- CryoRASS storage for this test = 425 CryoRASS + 425 CryoASFS + 300 ZL
 - For 96 hours, can flow $(1150 \times 728) = 837,200 \text{ liters gaseous}$ ($29,600 \text{ ft}^3$)
 - → **maximum** flow rate (for 96 hr) = 145 liters/minute (5.1 SCFM)
 - to provide maximum cooling and dehumidification



CryoRASS Prototype 1




John F. Kennedy Space Center



Liquid Air 425 liter dewar


Cryocooler behind panel



Air Handler box with duct work



How was CryoRASS tested?




John F. Kennedy Space Center


Test plan for CryoRASS in Experimental Mine

- Commercially available, inflatable Refuge chamber
- Instrument for temperatures, pressure, humidity
- Use “barrel person” simulator to generate heat and water vapor
 - Add 494 BTU/person
 - Add 1.3 liter water /person/day
- Conduct 96 (continuous) hour test
- Isolate chamber in cross-cut with insulated walls
- Digitally record all data
- Test conducted by Pittsburgh OMSHR personnel
- BCS/LABtech support on site for operation of CryoRASS

John F. Kennedy Space Center




John F. Kennedy Space Center




Air Handler Box
- liquid air input from bottom

Air duct from air handler (right)
Note "barrel persons" (left)





Testing of CryoRASS



John F. Kennedy Space Center



RASS connected to 23 man Inflatable chamber



**Test Instrumentation
& video monitoring**





Air Temperature



Plotted is the average and standard deviations of three temperature readings inside the refuge chamber (Front, middle, end) for each test. The data was collected at 1 sample/20 sec and re-sampled post-test 1 sample/ 5 minutes.





Relative Humidity



Plotted is the average and standard deviations of three Humidity readings inside the refuge chamber (Front, middle, end) for each test. The data was collected at 1 sample/20 sec and re-sampled post-test 1 sample/5 minutes.




Apparent Temperature



Plotted is the apparent temperature calculated by using the Wet Globe Bulb Temp approximation. The average and standard deviations of Three Humidity/Temperature readings inside the refuge chamber (Front, middle, end) was used for the WGBT calculation.



Test Results Summary




John F. Kennedy Space Center

- Actual (dry bulb) temperatures were marginally lower (- 3° F)
- Considerable humidity removed (~ 11 gal + ~ 1 gal frost + 3.4 gal expelled out through relief valve and/or leaks)
 - RH down to 85%
 - RH down to 76% at duct outlet
- Apparent temperature reduction:
 - Baseline: 74°F, 94% RH = 83.1°F Apparent
 - CryoRASS: 73°F, 85% RH = 77.2°F Apparent
 - **Overall apparent temperature reduction: 6°F**
- No effort was made to model or control CO₂




Conclusion




John F. Kennedy Space Center

- This test proved concept feasibility and prototype design
- CryoRASS system creates refuge air circulation (~ 150 SCFM)
- Since 140 liters/min (5.1 SCFM) added, then 140 l/m (w/water vapor + CO₂) expelled
- Temperature and humidity reduced
- Heat stress relief provided (6°F apparent temp reduction)
- Safety enhanced (low pressure air source)
- Air source space & weight requirement decreased
- Although not specifically tested here, increased airflow will purge CO₂, reducing the CO₂ levels in the chamber, thus reducing the need for CO₂ scrubbing. Since CO₂ scrubbing is a significant exothermic reaction, any reduction in the CO₂ concentration will result in additional heat savings.



Note dry
floor in tent 2 & 3

John F. Kennedy Space Center




Air handler, cold plate
and condensate tank



Partially dry
floor in tent 1



What's next?



John F. Kennedy Space Center

CryoRASS Prototype #2 will:


- Add second cold plate to air handler box
- Change to 1000 liter horizontal dewar (low seam mines)
- Ruggedize construction to comply with MSHA
- Larger, ruggedized cryocooler
- Design to fit existing inflatable, hard chambers, and “built in place”
 - Options
 - Stand alone CryoRASS connected to inflatable, hard refuge, or built in place
 - Fit CryoRASS components into inflatable’s storage box
 - Fit CryoRASS components into airlock of hard refuge
- Include Air Curtain at entryway vs. purge (next page)

John F. Kennedy Space Center



Video clip
of air curtain

Vent tubes




Measuring
air flow
from air
curtain





Questions?



John F. Kennedy Space Center

